

JALFIR 00JJE41

Softane

Adventure

S3 AN SC CI LG FO SR
EN ISO 20345:2022
35 to 48



- **Water-repellent full grain leather**
- **Softane™ PU double density insole**
- **Type B polymer tip / Steel anti-perforation**
- **Antistatic**

- ❖ High-top safety shoe in outdoor style, **suitable for the building sector**. Brown/ black color.
- ❖ Full-grain leather upper with water-repellent pull-up finish 1,8 / 2,0 mm. **Excellent waterproof leather, no water crossing after 7h test**. Very good breathability (sweating well above the normative requirements).
- ❖ The polyurethane toe cap, having been **SC-rated**, complies with **EN ISO 20345:2021**, which guarantees the footwear's sturdiness and longevity, as well as its increased resistance to impacts and scuffing.
- ❖ **Ankle protector**, protection of the malleoli against side impacts and anti-torsion reinforcement for the ankles. Average value 5.5 kN (the standard requires an average value of results <10 kN and no value >15 kN).
- ❖ Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ❖ Fastening by lacing on 4 pairs of metal shoelaces and 2 pairs of open hooks. Lace 130 cm.
- ❖ Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- ❖ Rear tug to facilitate fitting.
- ❖ **Soft** footbed made of **BASF® Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- ❖ **Ergonomic shoe** with broad toe-cap **SPRINGTANE type B** polymer tip for weight savings (50% lighter than steel). Resistant to a shock of 200 Joules. Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with **Standard 22568-2:2019**.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **Stainless rustproof steel midsole**.
- ❖ **Dual density Softane™ PU sole, robust and versatile**, with progressive shock absorber and anti-twist heel reinforcement integrated. Pu reinforcement to the front of the sole. Sole features with the **JAL'GRIP SYSTEM**, a **LADDER GRIP** double-release unhooking system as standard, is fully **LG-rated** in compliance with standard **EN ISO 20345:2021**, which enables ladder attachment and prevents the risk of falls from heights.

Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,36** (≥0,31)
B- Front to back **0,42** (≥0,36)

Additional requirement SR : Ceramic / Glycerin

C - Heel to the front **0,23** (≥0,19)
D- Front to back **0,33** (≥0,22)

- Density : comfort layer = 0.45 / Wear layer = 1.10.
- High resistance to abrasion.
- Very good resistance to oils and hydrocarbons.
- Absorption of the heel kick > 20 Joules.
- Deep cleats (6.5 mm) and self-cleaning.
- Large support surface for optimal stability.

Weight	Gross weight (42) : 1628 g / Net weight (42) : 1420 g			
Size	35 to 39	40	41 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	335 x 210 x 130		335 x 244 x 130	
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	685 x 256 x 356



 **Jallatte®**