

# DANUBE S3



**SRC** [0% METAL]

Standard EN ISO 20345 : 2011

## LEMAITRE

*Safety since 1974*



### THE PLUS PRODUCT

0% metal model. Suitable for areas equipped with metal detectors (warehouses,...).

Size 35 to 50

Réf. DANUS30BR

## Product Highlights



▪ **2,0 mm thick high strength leather:** against abrasion, tearing and puncture.

▪ **Anti-abrasion upper,** additional resistance of the stem on the forefoot that ensures a long life to the product.

▪ **Tongue with gusset** to prevent the intrusion of dust inside the shoe.



▪ **Comfort sole with shock absorbing heel pad:** reduction of impact and fatigue, prevention of MSD.

▪ **Extreme size coverage:** model available up to size 50.



▪ **Protective toe-cap:** polycarbonate.



▪ **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



## C07 PU2D antistatic sole

▪ **Wide and comfortable shoe**

▪ **Versatility:** effective spikes on industrial floors and outdoor surfaces

▪ **Extended contact area and 10 mm offset heel:** self-cleaning and multi-functional sole with excellent stability

▪ **Rounded heel attack** for a natural rolling of the foot


## USAGE

▪ Indoor and outdoor use: excellent versatility.



[lemaitre-securite.com](http://lemaitre-securite.com)

Lemaitre takes care.



# DANUBE S3



Standard EN ISO 20345 : 2011

## Characteristics of the upper

- **Matière du dessus** : water-repellent oiled split leather with abrasion-resistant uppers
- **Tongue with gusset**: abrasion resistant textile
- **Lining**: 3D microporus fabric

## Characteristics of the sole

- **Designation**: C07
- **Material**: polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient**:  
forward flat slip: 0,32 (standard  $\geq 0,32$ )  
forward heel slip: 0,29 (standard  $\geq 0,28$ )
- **SRB Adhesion coefficient**:  
forward flat slip: 0,18 (standard  $\geq 0,18$ )  
forward heel slip: 0,15 (standard  $\geq 0,13$ )

## VARIANT



**Douro S3 SRC**  
DOURS30BR

## Practical information

Weight of one shoe size 42: 630 g

**CERTIFICATION N°**201/2024/PPE/1439/B

## Packaging

### size 35 to 42

**shoebox** 315 x 220 x 125 mm

**carton** 635 x 445 x 325 mm

10 shoeboxes per carton

### size 43 to 50

**shoebox** 355 x 220 x 130 mm

**carton** 660 x 450 x 360 mm

10 shoeboxes per carton

## Gencods

<b>35</b>	3237154053355	<b>43</b>	3237154053430
<b>36</b>	3237154053362	<b>44</b>	3237154053447
<b>37</b>	3237154053379	<b>45</b>	3237154053454
<b>38</b>	3237154053386	<b>46</b>	3237154053461
<b>39</b>	3237154053393	<b>47</b>	3237154053478
<b>40</b>	3237154053409	<b>48</b>	3237154053485
<b>41</b>	3237154053416	<b>49</b>	3237154053492
<b>42</b>	3237154053423	<b>50</b>	3237154053508

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



**SRC = SRA + SRB**

**Lemaitre Sécurité**

17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

[lemaitre-securite.com](http://lemaitre-securite.com)

**LEMAITRE**

*Safety since 1974*

Member of  
**SINAMAP**



**DON\_LS 04 TDS 0116**  
update: 28/11/24